

Deep-Acting Primer

Universal Primer



Dispersion Primer for the Pre-Treatment of Absorbent Surfaces

Technical Data Sheet
No. 11.DAP
15.11.2009

Characteristics

- Ready to use
- Controls absorbency
- Vapour permeable
- Increases surface strength
- For internal & external use

Scope of use

Dispersion primer for use on highly absorbent masonry and concrete substrates, such as brick/concrete block prior to the application of Sempre Adhesive and basecoat, e.g. TU-100 Adhesive and TU-200 Adhesive & Basecoat. Sempre Deep-Acting Primer is for the pre-treatment of absorbent surfaces, reducing porosity and improving surface strength, especially after suitable preparation, e.g. brush clean, mechanical preparation, jet/pressure washing or blasting.

Substrate preparation

The selection of the appropriate priming system is dependent upon the substrate and its condition. The substrate must be free from structural defects, sound, i.e. of adequate compressive and tensile strength, dry and free from laitance, dust, debris, grease or other contamination that would impair the bond of the product. Where required mechanical methods of surface preparation should be adopted.

Application

Do not dilute the product. Decant the product into a roller tray or bucket. Apply to the prepared substrate with a roller or brush. Apply evenly, coating the whole area. Allow to dry before proceeding. Sempre Deep-Acting Primer will dry in approximately 4 hours. Very absorbent substrates may require a second application.

Storage

Up to 12 months since the production date when stored in cold conditions and in original undamaged packages.

Protect against frost!

Packaging

5 ltr, 10 ltr containers



Technical data

Base:	polymer dispersion
Bulk density:	approx. 1,0 gr / cm ³
Colour:	clear
Temperature of application:	from +5 °C to +30 °C
Drying time:	approx. 4 h
Application:	apply with a brush or roller
Estimated consumption:	approx. 0,2 ltr / m ² depending on the smoothness and absorption of the substrate

This product possesses:

- within the SempreTherm System: ETA – 08/0316
- NSAI Agreement Certificate No. 11/0358

Should you need support or advice, please consult our advisory service for architects and contractors on the hotline number:

ROI Phone: + 353 68 304 35
UK Phone: +44 20 3195 3880
PL Phone: +48 33 496 06 09

Manufacturer:

SEMPRE FARBY SP. z o.o.
Ul. Gen. Kustronia 60
43-301 Bielsko-Biała, Poland
tel: +48 33 496 06 09
fax: + 48 33 496 06 10
e-mail: info@semprefarby.pl
www.semprefarby.pl

ROI Distributor:

Sempre Therm Ireland Ltd
Abbeyfeale
Co. Limerick
tel: +353 68 304 35
mobile: +353 87 62 55 603
e-mail: info@sempretherm.ie
www.sempretherm.ie

UK Distributor:

Energytherm
Suite 1333, Kemp House, 152-160 City Road
EC1V 2NX, United Kingdom
tel: 00 44 (0) 20 3195 3880
mobile: 00 44 (0) 77 6784 1143
e-mail: tom@energytherm.co.uk
www.energytherm.co.uk