

# Sempre Eterna Acrylic Paint

Designed to paint buildings façades



Technical Data Sheet  
No. 3-SEAP  
01.03.2009

## Characteristics

- resistant to alkalis
- resistant to weather conditions
- resistant to biological corrosion
- easy to use
- available in 280 colours

## Scope of use

Sempre Eterna Paint is used for protecting façades, concrete constructions. It can be applied on the mineral substrates (concrete, sand & cement plasters, lime-cement plasters and lime plasters). This paint can be used for painting Sempre Tesoro acrylic renders applied on traditional substrates and within Sempre Therm ETICS (External Thermal Insulation Composite Systems) with the application of EPS-boards (Expanded Polystyrene boards). The façades covered with the paint Eterna can be washed with washing devices operating under low pressure. The exposure of the façade to the sun causes dangerous tensions, therefore dark colours should be used only on small areas, e.g. architectural details.

## Substrate preparation

The Sempre Eterna may be applied on carrying, smooth, dry and clean substrates ( free from any substances that decrease adhesion such as grease, bitumen, dust ):

- concrete (age over 28 days)
- traditional sand & cement plasters, lime-cement plasters and lime plasters (age over 14 days),
- thin-layer mineral and mineral-polymer plasters (age over 7 days),
- thin-layer acrylic plasters (age over 3 days),
- strong paint coats with good adhesion to the substrate.

Firstly uneven and damaged substrates should be repaired.

Sempre TU-200 can be used for repairs. It is recommended to check the strength of the existing mineral layers. The existing dirt, layers of low strength, lime and adhesive paint coatings as well as the remainders of wall paper or glues should be completely removed.

It is recommended to use washing devices. After being washed with water, the substrate should dry.



## Application

Before the paint application, the content of the container should be carefully stirred by means of the drill with a mixer for about 2 minutes. Usually it is sufficient to paint twice. Between the application of the subsequent layers the 4- to 6-hour technological breaks should be maintained. Sempre Eterna should be applied by means of a brush, roller or a sprinkling device. It is important to apply the paint evenly. If there is such a need, it is possible to add not more than 10% of water and stir carefully. Use only stainless containers and tools. Work on one surface should be carried on without any breaks using the paint of the same badge number printed on each packaging or the content of containers with different badge numbers should be mixed together. The area not to be painted, e.g. windows, doors should be protected (e.g. with foil). Bushes, other plants, etc. should be protected as well. Any stains should be immediately rinsed with water. Tools should be washed carefully with water directly after being used.

## Other information

This paint should not be applied on highly insulated surfaces.  
This product should not be mixed with other paints, pigments or binders.  
The facade should be protected against rain until the paint dries completely.

It is recommended to use scaffolding protection. The opened container should be carefully closed and its content should be used as soon as possible.

This technical data sheet determines the scope of application of the material and the way of conducting the work, however, it cannot replace the professional preparation of the contractor.

Apart from the data provided, the application should be done in compliance with the construction and industrial safety regulations. The manufacturer guarantees the quality of the product, however, he does not have any influence on the condition and the way of application. In case of any doubts, individual application trials should be conducted. The previously issued technical data sheets become invalid with the issue of this technical data sheet.

## Please note

Application should be performed in dry conditions with the ambient and substrate temperature ranging from +5 to +25 °C and the humidity below 80 %. All the data refer to the temperature of +20 °C and relative humidity of 60 %. Faster or slower drying of this product may occur in different conditions. The paint may cause decolouration impossible to be removed on glass, ceramic, wooden, metal and stone surfaces, therefore all the elements in contact with Sempre Eterna should be protected. Skin and eyes should be protected. Protective gloves and glasses should be worn while applying the paint. Stains should be carefully rinsed with water. In case of contact with eyes, they should be rinsed with water and the general practitioner should be consulted. This product should be stored out of reach of children.

## Storage

Up to 12 months from the production date when stored in cold conditions and in original undamaged packages.

**Protect against frost!**

## Packaging

5 ltr , 10 ltr buckets,

## Technical data

Base:	water dispersion of acrylic resins with mineral fillers
Bulk density:	1,50 gr / cm <sup>3</sup>
Pigments:	Titanium white and UV-resistant.
Temperature of application:	from +5 °C to +30 °C
Drying time:	approx. 3 h
Application:	apply with a brush, roller or spray gun
Estimated consumption:	approx. 0,25 ltr / m <sup>2</sup> depending on the smoothness and absorption of the substrate

This product possesses:

- ETA - 08/0316
- NSAI Agreement Certificate No.- 11/0358

**Should you need support or advice, please consult our advisory service for architects and contractors on the hotline number:**

**ROI Phone: + 353 68 304 35**  
**UK Phone: +44 20 3195 3880**  
**PL Phone: +48 33 496 06 09**

Apart from the information given here it is also important to observe the relevant guidelines and regulations of various organisations and trade associations as well as the respective standards. The aforementioned characteristics are based on practical experience and applied testing. Warranted properties and possible uses which go beyond those warranted in this information sheet require our written confirmation. All data given was obtained at an ambient and material temperature of +23 °C and 50 % relative air humidity unless specified otherwise. Please note that under other climatic conditions hardening can be accelerated or delayed.

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.

### Manufacturer:

**SEMPRE FARBY SP. z o.o.**

Ul. Gen. Kustronia 60  
43-301 Bielsko-Biała, Poland  
tel: +48 33 496 06 09  
fax: + 48 33 496 06 10

**e-mail: [info@semprefarby.pl](mailto:info@semprefarby.pl)**

**[www.semprefarby.pl](http://www.semprefarby.pl)**

### ROI Distributor:

**Sempre Therm Ireland Ltd**

Abbeyfeale  
Co. Limerick  
tel: +353 68 304 35  
mobile: +353 87 62 55 603

**e-mail: [info@sempretherm.ie](mailto:info@sempretherm.ie)**

**[www.sempretherm.ie](http://www.sempretherm.ie)**

### UK Distributor:

**Energytherm**

Suite 1333, Kemp House, 152-160 City Road  
EC1V 2NX, United Kingdom  
tel: 00 44 (0) 20 3195 3880  
mobile: 00 44 (0) 77 6784 1143

**e-mail: [tom@energytherm.co.uk](mailto:tom@energytherm.co.uk)**

**[www.energytherm.co.uk](http://www.energytherm.co.uk)**