

Deep-Acting Primer

Universal Primer



Dispersion Primer for the Pre-Treatment of Absorbent Surfaces

Technical Data Sheet
No. 11.DAP
15.11.2009

Characteristics

- Ready to use
- Controls absorbency
- Vapour permeable
- Increases surface strength
- For internal & external use

Scope of use

Dispersion primer for use on highly absorbent masonry and concrete substrates, such as brick/concrete block prior to the application of Sempre Adhesive and basecoat, e.g. TU-100 Adhesive and TU-200 Adhesive & Basecoat. Sempre Deep-Acting Primer is for the pre-treatment of absorbent surfaces, reducing porosity and improving surface strength, especially after suitable preparation, e.g. brush clean, mechanical preparation, jet/pressure washing or blasting.

Substrate preparation

The selection of the appropriate priming system is dependent upon the substrate and its condition. The substrate must be free from structural defects, sound, i.e. of adequate compressive and tensile strength, dry and free from laitance, dust, debris, grease or other contamination that would impair the bond of the product. Where required mechanical methods of surface preparation should be adopted.

Application

Do not dilute the product. Decant the product into a roller tray or bucket. Apply to the prepared substrate with a roller or brush. Apply evenly, coating the whole area. Allow to dry before proceeding. Sempre Deep-Acting Primer will dry in approximately 4 hours. Very absorbent substrates may require a second application.

Storage

Up to 12 months since the production date when stored in cold conditions and in original undamaged packages.
Protect against frost!

Packaging

5 ltr , 10 ltr containers



Technical data

Base:	polymer dispersion
Bulk density:	approx. 1,0 gr / cm ³
Colour:	clear
Temperature of application:	from +5 °C to +30 °C
Drying time:	approx. 4 h
Application:	apply with a brush or roller
Estimated consumption:	approx. 0,2 ltr / m ² depending on the smoothness and absorption of the substrate

This product possesses:

- within the SempreTherm System: ETA - 08/0316
- NSAI Agrément Certificate No.- 11/0358

**Should you need support or advice, please consult our advisory service for architects and contractors on the hotline number:
Phone: +353 61 40 30 811
e-mail: info@sempretherm.ie**

neotherm
approved distributor **sempre therm**

www.neotherm.ie

www.sempretherm.ie

info@neotherm.ie

Manufacturer: Sempre Farby Sp. z o.o.
ul. Gen. Kustronia 60, Bielsko-Biala, Poland
+48 33 496 06 09, info@semprefarby.pl

Dublin: Unit 31 Crag Avenue,
Clondalkin Industrial Est., Dublin 22
Office: 01 40 30 811

Limerick: Unit 5 Garryglass Industrial Est.
Ballysimon, Limerick
Office: 061 319 721